DOWNLIGHT

Avon One

Avon One Fire Rated Downlight 5W 3000K IP65 White 60D

Product code **430650**



Power	**5W**
Luminous flux	**550 lm**
Efficacy	**110 lm/W**
Colour temperature	**3000K**
Beam angle	**60°**
Protection	**65/20 · IK06**

Introduction

Single CCT Downlight, IP65, 110lm/W

Recommended applications

Offices, corridors, retail, hospitality

Specification

Optical

Luminous flux	**550 lm**
Efficacy	**110 lm/W**
Colour temperature	**3000K**
Beam angle	**60°**

Electrical

Power	**5W**
Supply voltage	**220-240V AC**

Construction

Ingress protection	**65/20**
Impact resistance	**IK06**
Electrical class	**Class II**
Body	**Aluminium**
Dimensions (L x W x H)	**84 x 84 x 50 mm**

Installation

Mounting	**BESA/Conduit**

Values are nominal. Luminous flux and efficacy are for the complete luminaire. Specifications may change without notice; the product page always carries the latest version.

Ordering information · Avon One

CODE	DESCRIPTION	POWER	LUMINOUS FLUX	EFFICACY	CCT	BEAM
430650	**Avon One Fire Rated Downlight 5W 3000K IP65 White 60D**	**5W**	**550**	**110 lm/W**	**3000K**	**60°**
430650-MP	Avon One Fire Rated Downlight 5W 3000K IP65 White 60D 8 Pack	5W	550	110 lm/W	3000K	60°
430651-MP	Avon One Fire Rated Downlight 5W 4000K IP65 White 60D 8 Pack	5W	550	110 lm/W	4000K	60°

DOWNLOADS

Photometric files (LDT), installation instructions and the latest datasheet are on the product page:

www.lumineux.co.uk/shop/430650-avon-one-fire-rated-downlight-5w-3000k-ip65-white-60d-54986

WARRANTY AND SUPPORT

Terms at www.lumineux.co.uk/product-warranty-on-site-warranty.

Free lighting design and technical support: 01507 328031, support@lumineux.co.uk