

# Technical Specification

**Category:** Wraysbury 1200x600


**Part Number:** 431274

**Description:** Wraysbury Backlit Panel 1200x600 48W 3CCT White  
UGR TP(a)



## Product Features:

- 600 x 600 & 1200 x 600 Backlit Panel
- 3CCT Selectable: 3000K, 4000K, 6000K
- Loch3 Quick Connector supplied
- Microprismatic TP (a) diffuser
- 5 Year Product Warranty
- 120 lm/W



## General information:

Wattage (W)	48
Lumens (lm)	5750
Efficacy (lm/W)	120
Colour Temperature (K)	3000 / 4000 / 6000
CCT	3CCT
IP Rating	40
IK Rating	3
Class Rating	2
Energy Rating	C
UGR	<19
Cut Out Size (mm) Ø	1180 x 590
Diffuser TP(a) / TP(b)	TP(a)
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	9003

## Technical information:


Application Location	Internal
Beam Angle	85
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	40
Product Warranty (Years)	5
Driver Brand	Lifud
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	Polystyrene
Install Options	BESA/Conduit
Install Type	Loch3 Quick Connector
Replaceable Driver	User
Replaceable LED	Professional
Body Material	Steel
Maintained	Maintained/Non-Maintained
Sensor Technology	Microwave

# Technical Specification

**Category:** Wraysbury 1200x600

**Part Number:** 431274

**Description:** Wraysbury Backlit Panel 1200x600 48W 3CCT White  
UGR TP(a)



## Compatible Products:



430971

Grafham 2W E-SEL3  
Emergency Conversion Pack  
20-55V DC 130mA LiFePO4  
3.2V DC 3.2 mAh Loch4  
Connector



430270

LED Multi Dimmable Driver  
42W-60W (Push Dim, 1-10V &  
DALI2) DC30-40V 1050-  
1500mA 200-240V Flicker  
Free



430148

Wraysbury Tool Free Pattress  
Kit 1200x600x70mm