

## Fontburn

**Category:** Fontburn

**Part Number:** 430953-WH

**Description:** Fontburn Emergency Exit Sign 2.5W 6500K White E-SEL3 Emergency



### Product Features:

- LiFePO4 battery
- White/Black polycarbonate body with polycarbonate legends
- Maintained
- E-SEL3 Manual / Self Test selection inside
- Included in Box: Side Mounting Arm, Suspension mounting kit, Recess mounting kit



### General information:

Wattage (W)	2.5
Lumens (lm)	45
Efficacy (lm/W)	20
Colour Temperature (K)	6500
IP Rating	20
IK Rating	3
Class Rating	2
Dimmable	Fixed
Paint Finish (RAL)	9016

### Technical information:

Application Location	Internal
Emergency Output (lm)	18
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	30
Product Warranty (Years)	5
SDCM	6
Driver Brand	Lumineux
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	PMMA
Install Options	BESA/Conduit
Install Type	Screw Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Maintained	Maintained
Viewing Distance (m)	24
Emergency Wattage (W)	2.5

## Fontburn

**Category:** Fontburn


**Part Number:** 430953-WH

**Description:** Fontburn Emergency Exit Sign 2.5W 6500K White E-SEL3 Emergency



### Technical information:

Emergency IP Rating	20
Cell Type	LiFePO4
Capacity (mAh)	600
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	45
Charge Current (mA)	90
Battery Size (V/Ah)	3.2 / 0.6
Battery Temperature (To) (°C)	30
Battery Length (mm)	65
Battery Width (mm)	18
Battery Height (mm)	18
Sensor Technology	Microwave



### Compatible Products:



430953-BL

Fontburn Emergency Exit Sign  
2.5W 6500K Black E-SEL3  
Emergency



430956

Fontburn Emergency Exit Sign  
Track Adapter



430944

Fontburn Exit Sign DOWN  
Legends (Pair)