

# Technical Specification

**Category:** Typhoon 3CCT


**Part Number:** 431317

**Description:** Typhoon Anti Corrosive 4ft Twin 18W/36W 3CCT IP65 Grey Plug & Play



## Product Features:

- Unique opal diffuser design for optimum performance and light distribution
- 160 lumens per watt
- Conduit entry points at both ends
- Suitable for central BESA mounting
- Pre-threaded M20 cable entry



## General information:

Wattage (W)	18 / 36
Lumens (lm)	3,050 / 6,125
Efficacy (lm/W)	170
Colour Temperature (K)	4000 / 5000 / 6000
CCT	3CCT
IP Rating	65
IK Rating	8
Class Rating	1
Energy Rating	B
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	7038

## Technical information:


Application Location	Internal
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-20
Operating Temperature To	40
Product Warranty (Years)	5
Driver Brand	Lifud
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Maintained	Maintained/Non-Maintained
Sensor Technology	Microwave

# Technical Specification

**Category:** Typhoon 3CCT

**Part Number:** 431317

**Description:** Typhoon Anti Corrosive 4ft Twin 18W/36W 3CCT IP65  
Grey Plug & Play



## Compatible Products:



430916

Alwen Linear Microwave  
Sensor 220-240V AC 200W  
Max Plug & Play



430962

Grafham 3.5W Conversion  
Pack 50-300V DC 0-40mA  
LifePO4 3.2V DC 3.2Ah Plug &  
Play E-SEL3 Emergency