ANTI-CORROSIVE

# Stanford

Stanford 6ft Twin Anti Corrosive - Grey Microwave

Product code **430037-MW**



| | |
|---|---|
| Power | **72W** |
| Luminous flux | **10,075 lm** |
| Efficacy | **140 lm/W** |
| Colour temperature | **5000K** |
| Beam angle | **120°** |
| Protection | **IP65 · IK08** |
| Lifetime L70 | **50,000 h** |
| Warranty | **5 years** |

## Introduction

4000K / 5000K, IP65, up to 140 lm/W.

## Features

- Anti-distortion housing
- Improved thermals utilising aluminium back PCBs
- Opal, ribbed polycarbonate diffuser to reduce glare
- Stainless steel clips
- H3 – High Output Emergency 440lm option available

## Certification and options

IP65 Ingress protection · IK08 Impact rating · UKCA marked · CE marked

## Recommended applications

Car parks, cold stores, food production, wash-down areas

# Specification

## Optical

| | |
|---|---|
| Luminous flux | **10,075 lm** |
| Efficacy | **140 lm/W** |
| Colour temperature | **5000K** |
| Colour rendering | **Ra 80** |
| Beam angle | **120°** |
| Flicker | **Flicker Free** |

## Electrical

| | |
|---|---|
| Power | **72W** |
| Supply voltage | **220-240V AC** |
| Frequency | **50 Hz / 60 Hz** |
| Driver type | **CC** |
| Driver | **Tridonic** |
| Dimming | **Fixed** |
| Standby power | **1.0 W** |

## Lifetime and warranty

| | |
|---|---|
| Lifetime L70 | **50,000 h** |
| Energy class | **D** |
| Warranty | **5 years** |
| Replaceable driver | **Professional** |
| Replaceable light source | **Professional** |

## Construction

| | |
|---|---|
| Ingress protection | **IP65** |
| Impact resistance | **IK08** |
| Electrical class | **Class I** |
| Body | **ABS** |
| Diffuser | **Polycarbonate** |
| Colour (RAL) | **RAL 830** |
| Location | **Internal** |
| Dimensions (L x W x H) | **1837 x 140 x 90 mm** |

## Installation

| | |
|---|---|
| Mounting | **BESA/Conduit** |
| Connection | **Screw Terminal** |
| Max. mounting height | **6 m** |
| Ambient temperature | **-20 to +40 °C** |

## Sensor and controls

| | |
|---|---|
| Detection radius | **10 x 4 m** |
| Hold time | **5s / 30s / 90s / 5min / 20min / 30min** |
| Technology | **Microwave** |
| Switching | **On-Off** |
| Grouping | **Standalone** |

Values are nominal. Luminous flux and efficacy are for the complete luminaire. Specifications may change without notice; the product page always carries the latest version.

## Dimensions




**4ft:** 1274mm, **5ft:** 1574mm
**6ft:** 1837mm

## Ordering information · Stanford

| CODE | DESCRIPTION | POWER | LUMINOUS FLUX | EFFICACY | CCT | BEAM |
|---|---|---|---|---|---|---|
| 430026 | Stanford 4ft Single Anti-Corrosive - Grey | 19W | 2,475 | 130 lm/W | 4000K | 120° |
| 430032 | Stanford 4ft Single Anti-Corrosive - Grey | 19W | 2,650 | 140 lm/W | 5000K | 120° |
| 430028 | Stanford 5ft Single Anti Corrosive - Grey | 27W | 3,500 | 130 lm/W | 4000K | 120° |
| 430034 | Stanford 5ft Single Anti Corrosive - Grey | 27W | 3,775 | 140 lm/W | 5000K | 120° |
| 430027 | Stanford 4ft Twin Anti-Corrosive - Grey | 38W | 4,950 | 130 lm/W | 4000K | 120° |
| 430033 | Stanford 4ft Twin Anti-Corrosive - Grey | 38W | 5,325 | 140 lm/W | 5000K | 120° |
| 430030 | Stanford 6ft Single Anti Corrosive - Grey | 38W | 4,950 | 130 lm/W | 4000K | 120° |
| 430036 | Stanford 6ft Single Anti Corrosive - Grey | 38W | 5,325 | 140 lm/W | 5000K | 120° |
| 430029 | Stanford 5ft Twin Anti Corrosive - Grey | 57W | 7,400 | 130 lm/W | 4000K | 120° |
| 430035 | Stanford 5ft Twin Anti Corrosive - Grey | 57W | 7,975 | 140 lm/W | 5000K | 120° |
| 430031 | Stanford 6ft Twin Anti Corrosive - Grey | 72W | 9,350 | 130 lm/W | 4000K | 120° |
| 430037 | Stanford 6ft Twin Anti Corrosive - Grey | 72W | 10,075 | 140 lm/W | 5000K | 120° |
| 430026-H3 | Stanford 4ft Single Anti-Corrosive - Grey High Output Emergency | 19W | 2,475 | 130 lm/W | 4000K | 120° |
| 430032-H3 | Stanford 4ft Single Anti-Corrosive - Grey High Output Emergency | 19W | 2,650 | 140 lm/W | 5000K | 120° |
| 430028-H3 | Stanford 5ft Single Anti Corrosive - Grey High Output Emergency | 27W | 3,500 | 130 lm/W | 4000K | 120° |
| 430034-H3 | Stanford 5ft Single Anti Corrosive - Grey High Output Emergency | 27W | 3,775 | 140 lm/W | 5000K | 120° |
| 430027-H3 | Stanford 4ft Twin Anti-Corrosive - Grey High Output Emergency | 38W | 4,950 | 130 lm/W | 4000K | 120° |
| 430033-H3 | Stanford 4ft Twin Anti-Corrosive - Grey High Output Emergency | 38W | 5,325 | 140 lm/W | 5000K | 120° |
| 430030-H3 | Stanford 6ft Single Anti Corrosive - Grey High Output Emergency | 38W | 4,950 | 130 lm/W | 4000K | 120° |
| 430036-H3 | Stanford 6ft Single Anti Corrosive - Grey High Output Emergency | 38W | 5,325 | 140 lm/W | 5000K | 120° |
| 430029-H3 | Stanford 5ft Twin Anti Corrosive - Grey High Output Emergency | 57W | 7,400 | 130 lm/W | 4000K | 120° |
| 430035-H3 | Stanford 5ft Twin Anti Corrosive - Grey High Output Emergency | 57W | 7,975 | 140 lm/W | 5000K | 120° |
| 430031-H3 | Stanford 6ft Twin Anti Corrosive - Grey High Output Emergency | 72W | 9,350 | 130 lm/W | 4000K | 120° |
| 430037-H3 | Stanford 6ft Twin Anti Corrosive - Grey High Output Emergency | 72W | 10,075 | 140 lm/W | 5000K | 120° |
| 430026-MW | Stanford 4ft Single Anti-Corrosive - Grey Microwave | 19W | 2,475 | 130 lm/W | 4000K | 120° |
| 430032-MW | Stanford 4ft Single Anti-Corrosive - Grey Microwave | 19W | 2,650 | 140 lm/W | 5000K | 120° |
| 430028-MW | Stanford 5ft Single Anti Corrosive - Grey Microwave | 27W | 3,500 | 130 lm/W | 4000K | 120° |
| 430034-MW | Stanford 5ft Single Anti Corrosive - Grey Microwave | 27W | 3,775 | 140 lm/W | 5000K | 120° |
| 430027-MW | Stanford 4ft Twin Anti-Corrosive - Grey Microwave | 38W | 4,950 | 130 lm/W | 4000K | 120° |
| 430033-MW | Stanford 4ft Twin Anti-Corrosive - Grey Microwave | 38W | 5,325 | 140 lm/W | 5000K | 120° |
| 430030-MW | Stanford 6ft Single Anti Corrosive - Grey Microwave | 38W | 4,950 | 130 lm/W | 4000K | 120° |
| 430036-MW | Stanford 6ft Single Anti Corrosive - Grey Microwave | 38W | 5,325 | 140 lm/W | 5000K | 120° |
| 430029-MW | Stanford 5ft Twin Anti Corrosive - Grey Microwave | 57W | 7,400 | 130 lm/W | 4000K | 120° |
| 430035-MW | Stanford 5ft Twin Anti Corrosive - Grey Microwave | 57W | 7,975 | 140 lm/W | 5000K | 120° |
| 430031-MW | Stanford 6ft Twin Anti Corrosive - Grey Microwave | 72W | 9,350 | 130 lm/W | 4000K | 120° |
| **430037-MW** | **Stanford 6ft Twin Anti Corrosive - Grey Microwave** | **72W** | **10,075** | **140 lm/W** | **5000K** | **120°** |

| CODE | DESCRIPTION | POWER | LUMINOUS FLUX | EFFICACY | CCT | BEAM |
|---|---|---|---|---|---|---|
| 430026-H3-MW | Stanford 4ft Single Anti-Corrosive - Grey High Output Emergency & Microwave | 19W | 2,475 | 130 lm/W | 4000K | 120° |
| 430032-H3-MW | Stanford 4ft Single Anti-Corrosive - Grey High Output Emergency & Microwave | 19W | 2,650 | 140 lm/W | 5000K | 120° |
| 430028-H3-MW | Stanford 5ft Single Anti Corrosive - Grey High Output Emergency & Microwave | 27W | 3,500 | 130 lm/W | 4000K | 120° |
| 430034-H3-MW | Stanford 5ft Single Anti Corrosive - Grey High Output Emergency & Microwave | 27W | 3,775 | 140 lm/W | 5000K | 120° |

**Code suffixes:** -MW Microwave sensor

## DOWNLOADS

Photometric files (LDT), installation instructions and the latest datasheet are on the product page:

**www.lumineux.co.uk/shop/430037-mw-stanford-anti-corrosive-6ft-twin-72w-5000k-ip65-grey-microwave-55607**

## WARRANTY AND SUPPORT

5 years warranty. Terms at www.lumineux.co.uk/product-warranty-on-site-warranty.

Free lighting design and technical support: 01507 328031, support@lumineux.co.uk