

# Technical Specification

**Category:** Stanford Single

**Part Number:** 430030-H3

**Description:** Stanford Anti-Corrosive 6ft Single 38W 4000K IP65  
Grey HO Emergency



## Product Features:

- Anti-distortion housing
- Improved thermals utilising aluminium back PCBs
- Opal, ribbed polycarbonate diffuser to reduce glare
- Stainless steel clips
- H3 – High Output Emergency 440lm option available



## General information:

Wattage (W)	38
Lumens (lm)	4950
Efficacy (lm/W)	130
Colour Temperature (K)	4000
IP Rating	65
IK Rating	8
Class Rating	1
Energy Rating	D
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	830

## Technical information:

Application Location	Internal
Emergency Output (lm)	440
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	30
Product Warranty (Years)	5
Driver Brand	Tridonic
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Screw Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	ABS
Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	4.0
Emergency IP Rating	20
Cell Type	IFR26650 - LiFePO4
Capacity (mAh)	3600
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	440
Charge Current (mA)	300
Battery Size (V/Ah)	6.4 / 3.6
Battery Temperature (To) (°C)	30

## Technical Specification

**Category:** Stanford Single

**Part Number:** 430030-H3

**Description:** Stanford Anti-Corrosive 6ft Single 38W 4000K IP65  
Grey HO Emergency



### Technical information:

Sensor Technology

Microwave

