

Technical Specification



Category: Sutton

Part Number: 430039-H3-PIR

Description: Sutton Batten 4ft Twin 38W 4000K White HO
Emergency & PIR Sensor



Product Features:

- Frosted, ribbed polycarbonate diffuser to reduce glare
- Improved thermals utilising aluminium back PCBs
- H3 - High Output Emergency 440lm option available
- Additional screw to secure end cap
- Push-fit terminals
- 20mm conduit entry



General information:

Wattage (W)	38
Lumens (lm)	5125
Efficacy (lm/W)	135
Colour Temperature (K)	4000
IP Rating	20
IK Rating	06
Class Rating	1
Energy Rating	C
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	9003

Technical information:

Application Location	Internal
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	40
Product Warranty (Years)	5
SDCM	5
Driver Brand	Lifud
Frequency (Hz)	50 60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Steel
Emergency Wattage (W)	3.5
Emergency IP Rating	20
Capacity (mAh)	3200
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	440
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 3.2
Battery Temperature (To) (°C)	30
Sensor Technology	PIR
Sensor Type	On-Off
Max. Mounting Height (m)	4

Technical Specification

Category: Sutton

Part Number: 430039-H3-PIR

Description: Sutton Batten 4ft Twin 38W 4000K White HO
Emergency & PIR Sensor



Technical information:

Hold Time	6s / 3min / 5min / 8min
Standby Power	0.5
Standalone/Grouping	Standalone

