


## Hawkridge

**Category:** Hawkridge

**Part Number:** 430698-M3S-DD

**Description:** Hawkridge Wall Pack 18W/28W 3CCT Black

Emergency Self Test Photocell



⚡ Wattage Selectable



IP65

IK08



### Product Features:

- Tough aluminium body with polycarbonate diffuser
- LED lifespan 50,000 hours L70
- Standard, emergency and dusk to dawn options available
- IK08 impact rated
- Selectable wattages
- No upward light



### General information:

Wattage (W)	18 / 28
Lumens (lm)	1,975 / 3,075
Efficacy (lm/W)	110
Colour Temperature (K)	3000 / 4000 / 6000
CCT	3CCT
IP Rating	65
IK Rating	08
Class Rating	1
Energy Rating	C
Dimmable	Fixed
L70 Hours	54000
L80 Hours	54000
Paint Finish (RAL)	7021

### Technical information:

Application Location	External
Optics	Asymmetric
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-20
Operating Temperature To	40
Product Warranty (Years)	5
SDCM	5
Driver Brand	Lumineux
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Terminal
Body Material	Aluminium

# Hawkridge

**Category:** Hawkridge

**Part Number:** 430698-M3S-DD

**Description:** Hawkridge Wall Pack 18W/28W 3CCT Black  
Emergency Self Test Photocell

