

# Technical Specification

**Category:** Holywell Plus


**Part Number:** 431291-E3

**Description:** Holywell Plus Batten 4ft Twin 18W/36W 3CCT White  
Plug & Play E-SEL3 Emergency



## Product Features:

- Single & Twin Outputs
- Unique opal diffuser design for optimum performance and light distribution
- Steel body construction with powder coat finish
- Conduit entry points at both ends
- Suitable for central BESA mounting
- Additional screw to secure end cap
- High efficiency 160lm/W



## General information:

Wattage (W)	18 / 36
Lumens (lm)	2,900 / 5,750
Efficacy (lm/W)	160
Colour Temperature (K)	3000 / 4000 / 6000
CCT	3CCT
IP Rating	20
IK Rating	06
Class Rating	1
Energy Rating	B
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	54000
L80 Hours	54000
L90 Hours	34000
Paint Finish (RAL)	9003

## Technical information:

Application Location	Internal
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	30
Product Warranty (Years)	5
SDCM	5
Driver Brand	Lifud
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Steel
Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	2.5
Emergency IP Rating	20
Cell Type	YH IFR18650 - LiFePO4
Capacity (mAh)	3200
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Charge Current (mA)	250
Battery Size (V/Ah)	3.2 / 3.2
Battery Temperature (To) (°C)	30
Module Length (mm)	170

## Technical Specification

**Category:** Holywell Plus

**Part Number:** 431291-E3

**Description:** Holywell Plus Batten 4ft Twin 18W/36W 3CCT White  
Plug & Play E-SEL3 Emergency



### Technical information:

Module Width (mm)	54
Module Height (mm)	32
Battery Length (mm)	1300
Battery Width (mm)	20
Battery Height (mm)	20
Battery Discharge (mA)	130

