

Technical Specification



Category: Typhoon 3CCT

Part Number: 431317-E3

Description: Typhoon Anti-Corrosive 4ft Twin 18W/36W 3CCT IP65
Grey Plug & Play E-SEL3 Emergency



Product Features:

- Unique opal diffuser design for optimum performance and light distribution
- 160 lumens per watt
- Conduit entry points at both ends
- Suitable for central BESA mounting
- Pre-threaded M20 cable entry



General information:

Wattage (W)	18 / 36
Lumens (lm)	3,050 / 6,125
Efficacy (lm/W)	170
Colour Temperature (K)	4000 / 5000 / 6000
CCT	3CCT
IP Rating	65
IK Rating	8
Class Rating	1
Energy Rating	B
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	7038

Technical information:

Application Location	Internal
Emergency Output (lm)	400
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	30
Product Warranty (Years)	5
Driver Brand	Lifud
Socket	N/A
Frequency (Hz)	50 60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	3.5

Technical Specification

Category: Typhoon 3CCT


Part Number: 431317-E3

Description: Typhoon Anti-Corrosive 4ft Twin 18W/36W 3CCT IP65
Grey Plug & Play E-SEL3 Emergency



Technical information:

Emergency IP Rating	20
Cell Type	IFR18650 - LiFePO4
Capacity (mAh)	3200
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	400
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 3.2
Battery Temperature (To) (°C)	30
Sensor Technology	Microwave



Compatible Products:



430916

Alwen Linear Microwave
Sensor 220-240V AC 200W
Max Plug & Play