

Rydal

Category: Rydal

Part Number: 431139-E3

Description: Rydal Wallpack 15W/22W/30W 3CCT IP65 Black E-SEL3 Emergency



Product Features:

- Dusk to Dawn option built in as standard
- Hinged front provides quick access & ease of installation
- Product can be wall mounted over a standard round BESA box, providing efficient & secure dual sided conduit cable entry points
- Rydal wallpack is designed to reduce light pollution using Asymmetric optics, perfect for outdoor lighting
- 3CCT Selectable: 3000K, 4000K, 5000K
- Asymmetric optic - 70° x 140°
- No upward light



General information:

Wattage (W)	15 / 22 / 30
Lumens (lm)	2250 / 3300 / 4500
Efficacy (lm/W)	150
Colour Temperature (K)	3000 / 4000 / 5000
CCT	3CCT
IP Rating	65
IK Rating	10
Class Rating	1
Energy Rating	C
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	870

Technical information:

Application Location	External
Emergency Output (lm)	300
Beam Angle	140x70
Optics	Asymmetric
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-20
Operating Temperature To	40
Product Warranty (Years)	5
Driver Brand	AGT
Socket	N/A
Frequency (Hz)	50 60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Aluminium

Rydal

Category: Rydal

Part Number: 431139-E3

Description: Rydal Wallpack 15W/22W/30W 3CCT IP65 Black E-SEL3 Emergency



Technical information:

Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	2.0
Emergency IP Rating	20
Cell Type	IFR18650 - LiFePO4
Capacity (mAh)	3200
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	450
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 3.2
Battery Temperature (To) (°C)	30
Battery Length (mm)	650
Battery Width (mm)	18
Battery Height (mm)	18
Sensor Technology	Microwave

