TRACK LIGHTING

Belvide

Belvide Spot Light 60D - Black DALI

Product code **460505-DA-WH**



Power	**20W**
Luminous flux	**2,250 lm**
Efficacy	**110 lm/W**
Colour temperature	**2700K / 4000K / 5000K**
Beam angle	**60°**
Protection	**IP20 · IK03**
Lifetime L70	**50,000 h**
Warranty	**5 years**

Introduction

Colour selectable, IP20, up to 110 lm/W.

Features

- 3CCT Selectable: 3000K, 4000K, 5000K
- Anti-glare track light
- Aluminium housing
- 5 Year Product Warranty

Certification and options

3CCT — Colour selectable
IP20 — Ingress protection
<19 UGR — Low glare UGR<19
UKCA — UKCA marked
CE — CE marked

Recommended applications

Retail, display, galleries

Specification

Optical

Luminous flux	**2,250 lm**
Efficacy	**110 lm/W**
Colour temperature	**2700K / 4000K / 5000K**
Colour rendering	**Ra 80**
Colour consistency	**6 SDCM**
Beam angle	**60°**
Glare (UGR)	**<19**
Flicker	**>1**

Construction

Ingress protection	**IP20**
Impact resistance	**IK03**
Electrical class	**Class I**
Body	**Aluminium**
Diffuser	**Polycarbonate**
Colour (RAL)	**RAL 9016**
Location	**Internal**
Dimensions (L x W x H)	**178 x 85 x 269 mm**

Electrical

Power	**20W**
Supply voltage	**220-240V AC**
Frequency	**50 Hz / 60 Hz**
Driver type	**CC**
Driver	**Lumineux**
Dimming	**TRIAC / DALI**

Installation

Mounting	**BESA/Conduit**
Connection	**Track**
Ambient temperature	**-20 to +45 °C**

Lifetime and warranty

Lifetime L70	**50,000 h**
Warranty	**5 years**
Replaceable driver	**Professional**
Replaceable light source	**Professional**

Values are nominal. Luminous flux and efficacy are for the complete luminaire. Specifications may change without notice; the product page always carries the latest version.

Ordering information · Belvide 240V Spot

CODE	DESCRIPTION	POWER	LUMINOUS FLUX	EFFICACY	CCT	BEAM
460504-BL	Belvide 240V 10W Spot Light 3CCT 60D Black	10W	1,100	110 lm/W	2700K / 4000K / 5000K	60°
460504-WH	Belvide 240V 10W Spot Light 3CCT 60D White	10W	1,100	110 lm/W	2700K / 4000K / 5000K	60°
460505-BL	Belvide Spot Light 60D - Black	20W	2,250	110 lm/W	2700K / 4000K / 5000K	60°
460505-WH	Belvide Spot Light 60D - White	20W	2,250	110 lm/W	2700K / 4000K / 5000K	60°
460506-BL	Belvide Spot Light 60D - Black	30W	3,050	110 lm/W	2700K / 4000K / 5000K	60°
460506-WH	Belvide Spot Light 60D - White	30W	3,050	110 lm/W	2700K / 4000K / 5000K	60°
460504-DA-WH	Belvide 240V 10W Spot Light 3CCT 60D White DALI	10W	1,100	110 lm/W	2700K / 4000K / 5000K	60°
460504-DA-BL	Belvide 240V 10W Spot Light 3CCT 60D Black DALI	10W	1,100	110 lm/W	2700K / 4000K / 5000K	60°
460505-DA-WH	**Belvide Spot Light 60D - Black DALI**	**20W**	**2,250**	**110 lm/W**	**2700K / 4000K / 5000K**	**60°**
460505-DA-BL	Belvide Spot Light 60D - Black DALI	20W	2,250	110 lm/W	2700K / 4000K / 5000K	60°
460506-DA-BL	Belvide Spot Light 60D - Black DALI	30W	3,050	110 lm/W	2700K / 4000K / 5000K	60°
460506-DA-WH	Belvide Spot Light 60D - Black DALI	30W	3,050	110 lm/W	2700K / 4000K / 5000K	60°

Code suffixes: -DA DALI dimming -BL Black finish -WH White finish

DOWNLOADS

Photometric files (LDT), installation instructions and the latest datasheet are on the product page:

www.lumineux.co.uk/shop/460505-da-wh-belvide-240v-20w-spot-light-3cct-60d-white-dali-60280

WARRANTY AND SUPPORT

5 years warranty. Terms at www.lumineux.co.uk/product-warranty-on-site-warranty.

Free lighting design and technical support: 01507 328031, support@lumineux.co.uk