

Woodhead All-In-One

Category: Woodhead All-in-One

Part Number: 431423-WH

Description: Woodhead All-In-One Downlight 2W White E-SEL3
Emergency



Product Features:

- Open Area & Corridor options available
- Black and White Bezel included
- LifePO4 battery
- E-SEL3 Manual / Self-Test selection inside
- Non-Maintained
- Recessed or surface installation
- Emergency: 300lm



General information:

| | |
|------------------------|-------|
| Wattage (W) | 2 |
| Lumens (lm) | 300 |
| Efficacy (lm/W) | 150 |
| Colour Temperature (K) | 6000 |
| IP Rating | 20 |
| IK Rating | 06 |
| Class Rating | 2 |
| Cut Out Size (mm) Ø | 113 |
| Diffuser TP(a) / TP(b) | - |
| Dimmable | Fixed |
| Paint Finish (RAL) | 9016 |

Technical information:

| | |
|----------------------------------|----------------|
| Application Location | Internal |
| Emergency Output (lm) | 300 |
| Beam Angle | 140 |
| CRI | 80 |
| Input Type | 220-240V AC |
| Driver Type | CC |
| Operating Temperature (°C) | 0 - +40 |
| Product Warranty (Years) | 5 |
| SDCM | 6 |
| Driver Brand | Luminaireux |
| Frequency (Hz) | 50 60 |
| Diffuser Material | Polycarbonate |
| Install Type | Flying Lead |
| Replaceable Driver | Professional |
| Replaceable LED | Professional |
| Body Material | Polycarbonate |
| Maintained | Non-Maintained |
| Emergency Wattage (W) | 2.0 |
| Cell Type | LiFePO4 |
| Recharge Time (Hours) | 24 |
| Emergency Duration (Hours) | 3 |
| Emergency Output (Standalone lm) | 300 |
| Battery Temperature (To) (°C) | 30 |

Woodhead All-In-One

Category: Woodhead All-in-One

Part Number: 431423-WH

Description: Woodhead All-In-One Downlight 2W White E-SEL3
Emergency

