


# Technical Specification

**Category:** Holywell Plus


**Part Number:** 431292-DA-E3

**Description:** Holywell Plus Batten 5ft Twin 25W/50W 3CCT White  
Plug & Play DALI Emergency



## Product Features:

- Single & Twin Outputs
- Unique opal diffuser design for optimum performance and light distribution
- Steel body construction with powder coat finish
- Conduit entry points at both ends
- Suitable for central BESA mounting
- Additional screw to secure end cap
- High efficiency 160lm/W



## General information:

Wattage (W)	25 / 50
Lumens (lm)	4,000 / 8,000
Efficacy (lm/W)	160
Colour Temperature (K)	3000 / 4000 / 6000
CCT	3CCT
IP Rating	20
IK Rating	06
Class Rating	1
Energy Rating	B
Flicker	Flicker Free
Dimmable	DALI
L70 Hours	54000
L80 Hours	54000
L90 Hours	34000
Paint Finish (RAL)	9003

## Technical information:

Application Location	Internal
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	40
Product Warranty (Years)	5
SDCM	5
Driver Brand	Helvar
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Steel
Cell Type	IFR18650 - LiFePO4
Capacity (mAh)	3200
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	400
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 3.2
Battery Temperature (To) (°C)	30

## Technical Specification

**Category:** Holywell Plus

**Part Number:** 431292-DA-E3

**Description:** Holywell Plus Batten 5ft Twin 25W/50W 3CCT White  
Plug & Play DALI Emergency

