


Technical Specification

Category: Holywell Plus


Part Number: 431292-DA-E3

Description: Holywell Plus Batten 5ft Twin 25W/50W 3CCT White
Plug & Play DALI Emergency



Product Features:

- Single & Twin Outputs
- Unique opal diffuser design for optimum performance and light distribution
- Steel body construction with powder coat finish
- Conduit entry points at both ends
- Suitable for central BESA mounting
- Additional screw to secure end cap



General information:

| | |
|------------------------|--------------------|
| Wattage (W) | 25 / 50 |
| Lumens (lm) | 4,000 / 8,000 |
| Efficacy (lm/W) | 160 |
| Colour Temperature (K) | 3000 / 4000 / 6000 |
| CCT | 3CCT |
| IP Rating | 20 |
| IK Rating | 06 |
| Class Rating | 1 |
| Energy Rating | B |
| Flicker | Flicker Free |
| Dimmable | DALI |
| L70 Hours | 54000 |
| L80 Hours | 54000 |
| L90 Hours | 34000 |
| Paint Finish (RAL) | 9003 |

Technical information:

| | |
|----------------------------------|--------------------|
| Application Location | Internal |
| Beam Angle | 120 |
| CRI | 80 |
| Input Type | 220-240V AC |
| Driver Type | CC |
| Operating Temperature To | 40 |
| Product Warranty (Years) | 5 |
| SDCM | 5 |
| Driver Brand | Helvar |
| Frequency (Hz) | 50 60 |
| Diffuser Material | Polycarbonate |
| Install Options | BESA/Conduit |
| Install Type | Push Fit Terminal |
| Replaceable Driver | Professional |
| Replaceable LED | Professional |
| Body Material | Steel |
| Cell Type | IFR18650 - LiFePO4 |
| Capacity (mAh) | 3200 |
| Recharge Time (Hours) | 24 |
| Emergency Duration (Hours) | 3 |
| Emergency Output (Standalone lm) | 400 |
| Charge Current (mA) | 300 |
| Battery Size (V/Ah) | 3.2 / 3.2 |
| Battery Temperature (To) (°C) | 30 |

Technical Specification

Category: Holywell Plus

Part Number: 431292-DA-E3

Description: Holywell Plus Batten 5ft Twin 25W/50W 3CCT White
Plug & Play DALI Emergency

