

Tamar

Category: Tamar

Part Number: 431353-DA-E3

Description: Tamar Anti-Corrosive 6ft Twin 30W/60W 4000K Grey
IP65 DALI & E-SEL3 Emergency



Product Features:

- Loop in - Loop out push-fit terminals
- Pre-threaded M20 cable entry
- Designed for easy and rapid installation
- Multiple conduit entry points



General information:

Wattage (W)	30 / 60
Lumens (lm)	4,800 / 9,600
Efficacy (lm/W)	160
Colour Temperature (K)	4000
IP Rating	65
IK Rating	8
Class Rating	1
Energy Rating	B
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	7047

Technical information:

Application Location	Internal
Emergency Output (lm)	400
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	30
Product Warranty (Years)	5
Driver Brand	Lifud
Socket	N/A
Frequency (Hz)	50 60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	3.5
Emergency IP Rating	20
Cell Type	IFR18650 - LiFePO4
Capacity (mAh)	3200
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	400
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 3.2
Battery Temperature (To) (°C)	30

Tamar

Category: Tamar

Part Number: 431353-DA-E3

Description: Tamar Anti-Corrosive 6ft Twin 30W/60W 4000K Grey
IP65 DALI & E-SEL3 Emergency



Technical information:

Sensor Technology

Microwave

