

Typhoon Anti-Corrosive

Category: Typhoon 3CCT

Part Number: 431318-MW

Description: Typhoon Anti-Corrosive 5ft Twin 25W/50W 3CCT IP65
 Grey Plug & Play Microwave



Product Features:

- Unique opal diffuser design for optimum performance and light distribution
- Conduit entry points at both ends
- Suitable for central BESA mounting
- Pre-threaded M20 cable entry



General information:

Wattage (W)	25 / 50
Lumens (lm)	4,250 / 8,500
Efficacy (lm/W)	170
Colour Temperature (K)	4000 / 5000 / 6000
CCT	3CCT
IP Rating	65
IK Rating	8
Class Rating	1
Energy Rating	B
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	7038

Technical information:

Application Location	Internal
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature (°C)	-20 - +40
Product Warranty (Years)	5
Driver Brand	Lifud
Socket	N/A
Frequency (Hz)	50 60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Sensor Technology	Microwave
Sensor Type	On-Off
Max. Mounting Height (m)	6
Hold Time	5 sec - 30 min

Typhoon Anti-Corrosive

Category: Typhoon 3CCT


Part Number: 431318-MW

Description: Typhoon Anti-Corrosive 5ft Twin 25W/50W 3CCT IP65
Grey Plug & Play Microwave



Technical information:

Detection Radius	1.5 - 5
Standby Power	0.5
Standalone/Grouping	Standalone



Compatible Products:



430916

Alwen Linear Microwave
Sensor 220-240V AC 200W
Max Plug & Play



430962

Grafham 3.5W Conversion
Pack 50-300V DC 0-40mA
LifePO4 3.2V DC 3.2Ah Plug &
Play E-SEL3 Emergency