

Avon Pro Gimbal Brushed Chrome

Category: Avon Gimbal

Part Number: 430862


Description: Avon Pro Fire Rated 360° Gimbal Downlight 4W/6W

4CCT IP54 Brushed Chrome 60D



Product Features:

- Wattage selectable: 4W/6W
- 4CCT selectable: 2700K, 3000K, 4000K, 6000K
- Complies with parts B, C, E and L of Building Regulations
- Suitable for solid or stranded cable Ø 0.75 – 2.5mm²
- Fully tested for 30, 60 and 90 minutes fire rated
- Meets STA Pattern Book fire test requirements
- Quick connector with LENNEL lever terminal
- Full 360° gimbal rotation
- 5 Year Product Warranty
- 130 lm/W



| Fire Rated | | | |
|-------------|--------|--------|--------|
| | 30 min | 60 min | 90 min |
| Solid Joist | • | • | • |
| Web joist | • | • | • |
| I Joist | • | • | • |

General information:

| | |
|------------------------|---------------------------|
| Wattage (W) | 4 / 6 |
| Lumens (lm) | 525 / 725 |
| Efficacy (lm/W) | 130 |
| Colour Temperature (K) | 2700 / 3000 / 4000 / 6000 |
| CCT | 4CCT |
| IP Rating | 54/20 |
| IK Rating | 6 |
| Class Rating | 2 |
| Energy Rating | D |
| Cut Out Size (mm) Ø | 75-80 |
| Flicker | Flicker Free |
| Dimmable | Triac |
| L70 Hours | 50000 |
| Paint Finish (RAL) | 9016 |

Technical information:

| | |
|----------------------------|---------------------------|
| Application Location | Internal |
| Beam Angle | 60 |
| CRI | 80 |
| Input Type | 220-240V AC |
| Driver Type | CC |
| Operating Temperature From | -10 |
| Operating Temperature To | 45 |
| Product Warranty (Years) | 5 |
| Driver Brand | Lumineux |
| Socket | N/A |
| Frequency (Hz) | 50 60 |
| Diffuser Material | Polycarbonate |
| Install Options | BESA/Conduit |
| Install Type | Lever Terminal |
| Replaceable Driver | No |
| Replaceable LED | No |
| Body Material | Aluminium |
| Maintained | Maintained/Non-Maintained |
| Sensor Technology | Microwave |

Avon Pro Gimbal Brushed Chrome

Category: Avon Gimbal

Part Number: 430862

Description: Avon Pro Fire Rated 360° Gimbal Downlight 4W/6W
4CCT IP54 Brushed Chrome 60D

