

Frankly Plus

Category: Frankly Plus


Part Number: 430976-DD

Description: Frankly Plus Floodlight 100W 4000K IP66 Black ASY
50x125D P55D Photocell



Product Features:

- 'A' rated product delivering over 180 lm/W
- Asymmetric optic - 50° x 120° P55D
- Supplied with 1.5M prewired H05RN-F cable
- Angled bracket for ease of installation
- 6kVA L/N-PE surge protection
- Diecast aluminium body
- Breather valve to prevent condensation



General information:

Wattage (W)	100
Lumens (lm)	18000
Efficacy (lm/W)	180
Colour Temperature (K)	4000
IP Rating	66
IK Rating	8
Class Rating	1
Energy Rating	A
Dimmable	Fixed
L70 Hours	60000
Paint Finish (RAL)	9017

Technical information:


Application Location	Both
Beam Angle	50 x 125
Optics	Asymmetric
CRI	70
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-20
Operating Temperature To	45
Product Warranty (Years)	5
Driver Brand	Lifud
Socket	N/A
Frequency (Hz)	50 60
Finish	Powder Coating
Diffuser Material	Polycarbonate Lens
Install Options	BESA/Conduit
Install Type	1.5m H05RN-F
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Aluminium
Maintained	Maintained/Non-Maintained
Sensor Technology	Photocell
Sensor Type	On-Off
Standby Power	0.5
Standalone/Grouping	Standalone

Frankly Plus

Category: Frankly Plus

Part Number: 430976-DD

Description: Frankly Plus Floodlight 100W 4000K IP66 Black ASY
50x125D P55D Photocell



WATTS	A	B	C
50W	344mm	269mm	65mm
75W	390mm	317mm	65mm
100W	390mm	317mm	65mm
150W	420mm	349mm	65mm
200W	459mm	387mm	65mm
240W	499mm	441mm	70mm
300W	499mm	441mm	70mm