

## Redbrook

**Category:** Redbrook


**Part Number:** 430952-BL

**Description:** Redbrook Emergency Exit Box 3.5W 6500K Black E-SEL3 Emergency



### Product Features:


- LiFePO4 battery
- 20mm conduit entry on side, rear & top
- E-SEL3 Manual / Self Test selection inside
- Included in Box 4 legends, up, down, left & right (ISO7010 Legends as Standard)



Conduit entry on side, rear & top



Task Light Emergency



4 legends, up, down, left & right

### General information:

Wattage (W)	3.5
Lumens (lm)	25
Colour Temperature (K)	6500
IP Rating	20
IK Rating	3
Class Rating	2
Dimmable	Fixed
Paint Finish (RAL)	9011

### Technical information:

Application Location	Internal
Emergency Output (lm)	90
CRI	80
Input Type	220-240V AC
Operating Temperature To	40
Product Warranty (Years)	5
Driver Brand	Lumineux
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Maintained	Maintained/Non-Maintained
Viewing Distance (m)	24
Emergency Wattage (W)	1.0
Emergency IP Rating	20

## Redbrook

**Category:** Redbrook

**Part Number:** 430952-BL

**Description:** Redbrook Emergency Exit Box 3.5W 6500K Black E-SEL3 Emergency



### Technical information:

Cell Type	YH IFR18650 - LiFePO4
Capacity (mAh)	1600
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	90
Charge Current (mA)	336
Battery Size (V/Ah)	3.2 / 1.6
Battery Temperature (To) (°C)	30
Battery Length (mm)	65
Battery Width (mm)	18
Battery Height (mm)	18
Battery Discharge (mA)	150
Sensor Technology	Microwave

