

Frankly Plus

Category: Frankly Plus

Part Number: 430977-DD

Description: Frankly Plus Floodlight 150W 4000K IP66 Black ASY
50x125D P55D Photocell



Product Features:

- 'A' rated product delivering over 180 lm/W
- Asymmetric optic - 50° x 120° P55D
- Supplied with 1.5M prewired H05RN-F cable
- Angled bracket for ease of installation
- 6kVA L/N-PE surge protection
- Diecast aluminium body
- Breather valve to prevent condensation



General information:

| | |
|------------------------|-------|
| Wattage (W) | 150 |
| Lumens (lm) | 27000 |
| Efficacy (lm/W) | 180 |
| Colour Temperature (K) | 4000 |
| IP Rating | 66 |
| IK Rating | 8 |
| Class Rating | 1 |
| Energy Rating | A |
| Dimmable | Fixed |
| L70 Hours | 60000 |
| Paint Finish (RAL) | 9017 |

Technical information:


| | |
|----------------------------|---------------------------|
| Application Location | Both |
| Beam Angle | 50 x 125 |
| Optics | Asymmetric |
| CRI | 70 |
| Input Type | 220-240V AC |
| Driver Type | CC |
| Operating Temperature From | -20 |
| Operating Temperature To | 45 |
| Product Warranty (Years) | 5 |
| Driver Brand | Lifud |
| Socket | N/A |
| Frequency (Hz) | 50 60 |
| Finish | Powder Coating |
| Diffuser Material | Polycarbonate Lens |
| Install Options | BESA/Conduit |
| Install Type | 1.5m H05RN-F |
| Replaceable Driver | Professional |
| Replaceable LED | Professional |
| Body Material | Aluminium |
| Maintained | Maintained/Non-Maintained |
| Sensor Technology | Photocell |
| Sensor Type | On-Off |
| Standby Power | 0.5 |
| Standalone/Grouping | Standalone |

Frankly Plus

Category: Frankly Plus

Part Number: 430977-DD

Description: Frankly Plus Floodlight 150W 4000K IP66 Black ASY
50x125D P55D Photocell



| WATTS | A | B | C |
|-------|-------|-------|------|
| 50W | 344mm | 269mm | 65mm |
| 75W | 390mm | 317mm | 65mm |
| 100W | 390mm | 317mm | 65mm |
| 150W | 420mm | 349mm | 65mm |
| 200W | 459mm | 387mm | 65mm |
| 240W | 499mm | 441mm | 70mm |
| 300W | 499mm | 441mm | 70mm |