

Hurworth

Category: Hurworth


Part Number: 430196-M3

Description: Hurworth Wallpack DieCast 30W 3CCT Black
Emergency



Product Features:

- Standard, emergency and dusk to dawn options available
- Hinged front cover for quick and easy installation
- Diecast body and tough polycarbonate diffuser
- LED lifespan 50,000 hours L70



General information:

Wattage (W)	30
Lumens (lm)	2700
Efficacy (lm/W)	90
Colour Temperature (K)	3000 / 4000 / 6000
CCT	3CCT
IP Rating	65
IK Rating	10
Class Rating	1
Energy Rating	F
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	9005

Technical information:

Application Location	External
Emergency Output (lm)	300
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-20
Operating Temperature To	40
Product Warranty (Years)	5
Driver Brand	Boke
Socket	N/A
Frequency (Hz)	50 60
Diffuser Material	Polycarbonate
Install Options	Conduit
Install Type	Push Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Aluminium
Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	2.0
Emergency IP Rating	20
Cell Type	IFR18650 - LiFePO4
Capacity (mAh)	2000
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	150
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 2

Hurworth

Category: Hurworth

Part Number: 430196-M3

Description: Hurworth Wallpack DieCast 30W 3CCT Black
Emergency



Technical information:

Battery Temperature (To) (°C)	30
Battery Length (mm)	650
Battery Width (mm)	18
Battery Height (mm)	18
Sensor Technology	Microwave

