

# Technical Specification

**Category:** Olton

**Part Number:** 430817

**Description:** Olton UGR Academic Batten 4ft 20W/38W 4000K White




⚡ **Wattage Selectable**

IP20

UK  
CA  
CE

## Product Features:

- UGR Opal, ribbed polycarbonate diffuser to reduce glare
- Switchable dual wattage batten
- Multi 20mm conduit entry
- 5 Year Product Warranty
- High output self-test emergency available
- Robust steel body construction



## General information:

Wattage (W)	20 / 38
Lumens (lm)	2,400 / 4,550
Efficacy (lm/W)	120
Colour Temperature (K)	4000
IP Rating	20
IK Rating	3
Class Rating	1
Energy Rating	C
UGR	<21
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	9003

## Technical information:

Application Location	Internal
Beam Angle	115
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	45
Product Warranty (Years)	5
Driver Brand	Lumineux
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Steel
Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	4.0
Emergency IP Rating	20
Cell Type	IFR26650 - LiFePO4
Capacity (mAh)	3600
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	440
Charge Current (mA)	300
Battery Size (V/Ah)	6.4 / 3.6
Battery Temperature (To) (°C)	30
Sensor Technology	Microwave

## Technical Specification

**Category:** Olton

**Part Number:** 430817

**Description:** Olton UGR Academic Batten 4ft 20W/38W 4000K White

