

# Technical Specification

**Category:** Holywell


**Part Number:** 431300-E3

**Description:** Holywell Batten 4ft Single 19W 4000K White Plug & Play E-SEL3 Emergency



## Product Features:

- Unique opal diffuser design for optimum performance and light distribution
- Steel body construction with powder coat finish
- Conduit entry points at both ends
- Suitable for central BESA mounting
- Additional screw to secure end cap



## General information:

Wattage (W)	19
Lumens (lm)	3050
Efficacy (lm/W)	160
Colour Temperature (K)	4000
IP Rating	20
IK Rating	6
Class Rating	1
Energy Rating	B
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	54000
L80 Hours	54000
L90 Hours	34000
Paint Finish (RAL)	9003

## Technical information:

Application Location	Internal
Emergency Output (lm)	400
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	30
Product Warranty (Years)	5
Driver Brand	Lifud
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Steel
Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	3.5
Emergency IP Rating	20
Cell Type	IFR18650 - LiFePO4
Capacity (mAh)	3200
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	400
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 3.2
Battery Temperature (To) (°C)	30

# Technical Specification

**Category:** Holywell

**Part Number:** 431300-E3

**Description:** Holywell Batten 4ft Single 19W 4000K White Plug & Play E-SEL3 Emergency



## Technical information:

Sensor Technology

Microwave

