

Hurworth Mini

Category: Hurworth Mini

Part Number: 431200-M3

Description: Hurworth Mini Wallpack 12W 3CCT Black IP65
Emergency



Product Features:

- Standard, emergency and dusk to dawn options available.
- Tough body construction with polycarbonate diffuser
- LED Lifespan 40,000 hours L70



General information:

| | |
|------------------------|--------------------|
| Wattage (W) | 12 |
| Lumens (lm) | 1250 |
| Efficacy (lm/W) | 105 |
| Colour Temperature (K) | 3000 / 4000 / 6000 |
| CCT | 3CCT |
| IP Rating | 65 |
| IK Rating | 8 |
| Class Rating | 1 |
| Energy Rating | D |
| Dimmable | Fixed |
| L70 Hours | 60000 |
| Paint Finish (RAL) | 9005 |

Technical information:

| | |
|----------------------------------|---------------------------|
| Application Location | External |
| Beam Angle | 110 |
| CRI | 80 |
| Input Type | 220-240V AC |
| Driver Type | CC |
| Operating Temperature From | -20 |
| Operating Temperature To | 40 |
| Product Warranty (Years) | 3 |
| Driver Brand | Lumineux |
| Socket | N/A |
| Frequency (Hz) | 50 60 |
| Diffuser Material | Polycarbonate |
| Install Options | BESA/Conduit |
| Install Type | Push Terminal |
| Replaceable Driver | Professional |
| Replaceable LED | Professional |
| Body Material | Polycarbonate |
| Maintained | Maintained/Non-Maintained |
| Emergency Wattage (W) | 2.0 |
| Emergency IP Rating | 20 |
| Cell Type | IFR18650 - LiFePO4 |
| Capacity (mAh) | 2000 |
| Recharge Time (Hours) | 24 |
| Emergency Duration (Hours) | 3 |
| Emergency Output (Standalone lm) | 150 |
| Charge Current (mA) | 300 |
| Battery Size (V/Ah) | 3.2 / 2 |
| Battery Temperature (To) (°C) | 30 |

Hurworth Mini

Category: Hurworth Mini

Part Number: 431200-M3

Description: Hurworth Mini Wallpack 12W 3CCT Black IP65
Emergency



Technical information:

| | |
|---------------------|-----------|
| Battery Length (mm) | 650 |
| Battery Width (mm) | 18 |
| Battery Height (mm) | 18 |
| Sensor Technology | Microwave |

