

Hurworth Mini

Category: Hurworth Mini

Part Number: 431200-M3

Description: Hurworth Mini Wallpack 12W 3CCT Black IP65
Emergency



Product Features:

- Standard, emergency and dusk to dawn options available.
- Tough body construction with polycarbonate diffuser
- LED Lifespan 40,000 hours L70



General information:

Wattage (W)	12
Lumens (lm)	1250
Efficacy (lm/W)	105
Colour Temperature (K)	3000 / 4000 / 6000
CCT	3CCT
IP Rating	65
IK Rating	8
Class Rating	1
Energy Rating	D
Dimmable	Fixed
L70 Hours	60000
Paint Finish (RAL)	9005

Technical information:

Application Location	External
Beam Angle	110
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-20
Operating Temperature To	40
Product Warranty (Years)	3
Driver Brand	Lumineux
Socket	N/A
Frequency (Hz)	50 60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	2.0
Emergency IP Rating	20
Cell Type	IFR18650 - LiFePO4
Capacity (mAh)	2000
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	150
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 2
Battery Temperature (To) (°C)	30

Hurworth Mini

Category: Hurworth Mini

Part Number: 431200-M3

Description: Hurworth Mini Wallpack 12W 3CCT Black IP65
Emergency



Technical information:

Battery Length (mm)	650
Battery Width (mm)	18
Battery Height (mm)	18
Sensor Technology	Microwave

