

# Technical Specification

**Category:** Tempest 2CCT

**Part Number:** 431342-DA

**Description:** Tempest Anti-Corrosive 6ft Twin 33W/62W 2CCT IP65  
Grey Plug & Play DALI



## Product Features:

- Opal diffuser
- Wattage Selectable and 2CCT
- Pre-threaded M20 cable entry
- Designed for easy and rapid installation



## General information:

Wattage (W)	33 / 62
Lumens (lm)	6,100 / 11,150
Efficacy (lm/W)	185
Colour Temperature (K)	4000 / 5000
CCT	2CCT
IP Rating	65
IK Rating	8
Class Rating	1
Energy Rating	A
Flicker	Flicker Free
Dimmable	DALI
L70 Hours	70000
Paint Finish (RAL)	7047

## Technical information:


Application Location	Internal
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-20
Operating Temperature To	45
Product Warranty (Years)	5
Driver Brand	Helvar
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Maintained	Maintained/Non-Maintained
Sensor Technology	Microwave

## Technical Specification

**Category:** Tempest 2CCT

**Part Number:** 431342-DA

**Description:** Tempest Anti-Corrosive 6ft Twin 33W/62W 2CCT IP65  
Grey Plug & Play DALI



4ft: 1240mm, 5ft: 1540mm, 6ft: 1840mm