

# Typhoon Anti-Corrosive

**Category:** Typhoon 3CCT

**Part Number:** 431318-E3

**Description:** Typhoon Anti-Corrosive 5ft Twin 25W/50W 3CCT IP65 Grey Plug & Play E-SEL3 Emergency



## Product Features:

- Unique opal diffuser design for optimum performance and light distribution
- Conduit entry points at both ends
- Suitable for central BESA mounting
- Pre-threaded M20 cable entry



## General information:

Wattage (W)	25 / 50
Lumens (lm)	4,250 / 8,500
Efficacy (lm/W)	170
Colour Temperature (K)	4000 / 5000 / 6000
CCT	3CCT
IP Rating	65
IK Rating	8
Class Rating	1
Energy Rating	B
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	50000
Paint Finish (RAL)	7038

## Technical information:

Application Location	Internal
Emergency Output (lm)	400
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature To	30
Product Warranty (Years)	5
Driver Brand	Lifud
Socket	N/A
Frequency (Hz)	50   60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Fit Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Maintained	Maintained/Non-Maintained
Emergency Wattage (W)	3.5

## Typhoon Anti-Corrosive

**Category:** Typhoon 3CCT


**Part Number:** 431318-E3

**Description:** Typhoon Anti-Corrosive 5ft Twin 25W/50W 3CCT IP65  
Grey Plug & Play E-SEL3 Emergency



### Technical information:

Emergency IP Rating	20
Cell Type	IFR18650 - LiFePO4
Capacity (mAh)	3200
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	400
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 3.2
Battery Temperature (To) (°C)	30



### Compatible Products:



430916

Alwen Linear Microwave  
Sensor 220-240V AC 200W  
Max Plug & Play