

## Pebley

**Category:** Pebley


**Part Number:** 431126-BL-E3

**Description:** Pebley Utility Square Bulkhead 12W/16W/18W 3CCT  
IP65 Black Plug & Play E-SEL3 Emergency



### Product Features:

- Standard, microwave, emergency, dusk to dawn and 3 step dimming options available
- Tough and durable body with polycarbonate prismatic diffuser
- Wall and ceiling mount
- LED lifespan 60,000 hours L70
- X4 20mm conduit entry points



### General information:

Wattage (W)	12 / 16 / 18
Lumens (lm)	1,325 / 1,750 / 1,975
Efficacy (lm/W)	110
Colour Temperature (K)	3000 / 4000 / 6000
CCT	3CCT
IP Rating	65
IK Rating	08
Class Rating	2
Energy Rating	D
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	60000
L80 Hours	40000
Paint Finish (RAL)	7021

### Technical information:

Application Location	Both
Beam Angle	140
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-20
Operating Temperature To	40
Product Warranty (Years)	5
SDCM	5
Driver Brand	Lumineux
Socket	N/A
Frequency (Hz)	50   60
Install Options	BESA/Conduit
Install Type	Push Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Polycarbonate
Maintained	Non-Maintained
Emergency Wattage (W)	2.0
Emergency IP Rating	20
Cell Type	YH IFR18650 - LiFePO4
Capacity (mAh)	2000
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	150
Charge Current (mA)	300
Battery Size (V/Ah)	3.2/ 2
Battery Temperature (To) (°C)	30

## Technical Specification

# Pebley

**Category:** Pebley



**Part Number:** 431126-BL-E3

**Description:** Pebley Utility Square Bulkhead 12W/16W/18W 3CCT  
IP65 Black Plug & Play E-SEL3 Emergency




### Technical information:

Module Length (mm)	125
Module Width (mm)	71
Module Height (mm)	31
Battery Length (mm)	650
Battery Width (mm)	20
Battery Height (mm)	20



### Compatible Products:



431127

Alwen Plug & Play MW Sensor  
(For Bulkheads)