

Technical Specification

Category: Tempest 2CCT

Part Number: 431341-E3

Description: Tempest Anti-Corrosive 5ft Twin 26W/46W 2CCT IP65
Grey Plug & Play E-SEL3 Emergency



Product Features:

- Opal diffuser
- Wattage Selectable and 2CCT
- Pre-threaded M20 cable entry
- Designed for easy and rapid installation



General information:

| | |
|------------------------|---------------|
| Wattage (W) | 26 / 46 |
| Lumens (lm) | 4,800 / 8,275 |
| Efficacy (lm/W) | 185 |
| Colour Temperature (K) | 4000 / 5000 |
| CCT | 2CCT |
| IP Rating | 65 |
| IK Rating | 8 |
| Class Rating | 1 |
| Energy Rating | A |
| Flicker | Flicker Free |
| Dimmable | Fixed |
| L70 Hours | 70000 |
| Paint Finish (RAL) | 7047 |

Technical information:

| | |
|--------------------------|---------------------------|
| Application Location | Internal |
| Emergency Output (lm) | 400 |
| Beam Angle | 120 |
| CRI | 80 |
| Input Type | 220-240V AC |
| Driver Type | CC |
| Operating Temperature To | 30 |
| Product Warranty (Years) | 5 |
| Driver Brand | Boke |
| Socket | N/A |
| Frequency (Hz) | 50 60 |
| Diffuser Material | Polycarbonate |
| Install Options | BESA/Conduit |
| Install Type | Push Fit Terminal |
| Replaceable Driver | Professional |
| Replaceable LED | Professional |
| Body Material | Polycarbonate |
| Maintained | Maintained/Non-Maintained |
| Emergency Wattage (W) | 3.5 |

Technical Specification

Category: Tempest 2CCT

Part Number: 431341-E3

Description: Tempest Anti-Corrosive 5ft Twin 26W/46W 2CCT IP65
Grey Plug & Play E-SEL3 Emergency



Technical information:

| | |
|----------------------------------|--------------------|
| Emergency IP Rating | 20 |
| Cell Type | IFR18650 - LiFePO4 |
| Capacity (mAh) | 3200 |
| Recharge Time (Hours) | 24 |
| Emergency Duration (Hours) | 3 |
| Emergency Output (Standalone lm) | 400 |
| Charge Current (mA) | 300 |
| Battery Size (V/Ah) | 3.2 / 3.2 |
| Battery Temperature (To) (°C) | 30 |
| Sensor Technology | Microwave |

