

Hollingworth Eyelid

Category: Hollingworth

Part Number: 431130-E3

Description: Hollingworth Diecast Eyelid Bulkhead 12W/16W/18W
3CCT Black Plug & Play IP65 E-SEL3 Emergency



Product Features:

- Standard, step dim microwave, emergency and dusk to dawn available
- Tough and durable diecast body with polycarbonate diffuser
- Wall and ceiling mount
- LED lifespan 60,000 hours L70



General information:

Wattage (W)	12 / 16 / 18
Lumens (lm)	600 / 800 / 960
Efficacy (lm/W)	50
Colour Temperature (K)	3000 / 4000 / 6000
CCT	3CCT
IP Rating	65
IK Rating	10
Class Rating	1
Energy Rating	F
Flicker	Flicker Free
Dimmable	Fixed
L70 Hours	60000
Paint Finish (RAL)	7021

Technical information:

Application Location	Internal
Emergency Output (lm)	100
Beam Angle	120
CRI	80
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-20
Operating Temperature To	40
Product Warranty (Years)	5
Driver Brand	Luminaireux
Socket	N/A
Frequency (Hz)	50 60
Diffuser Material	Polycarbonate
Install Options	BESA/Conduit
Install Type	Push Terminal
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Aluminium
Maintained	Non-Maintained
Emergency Wattage (W)	2.0
Emergency IP Rating	20
Cell Type	YH IFR18650 - LiFePO4
Capacity (mAh)	2000
Recharge Time (Hours)	24
Emergency Duration (Hours)	3
Emergency Output (Standalone lm)	150
Charge Current (mA)	300
Battery Size (V/Ah)	3.2 / 2

Hollingworth Eyelid

Category: Hollingworth



Part Number: 431130-E3

Description: Hollingworth Diecast Eyelid Bulkhead 12W/16W/18W
3CCT Black Plug & Play IP65 E-SEL3 Emergency




Technical information:

Battery Temperature (To) (°C)	30
Module Length (mm)	125
Module Width (mm)	71
Module Height (mm)	31
Battery Length (mm)	650
Battery Width (mm)	20
Battery Height (mm)	20



Compatible Products:



431127

Alwen Plug & Play MW Sensor
(For Bulkheads)