

Thoresby

Category: Thoresby

Part Number: 421385

Description: Thoresby Floodlight 60W/80W/100W 3CCT IP66 Black
ASY 50x120D P55D



Wattage Selectable

IP66

IK08



Dusk to Dawn



Product Features:

- Wattage Selectable
- 3CCT Selectable: 3000K, 4000K, 5000K
- Dusk till dawn built in as standard.
- Asymmetric Optics
- IP66 & IK08 Rated
- Supplied with 1M prewired H05RN-F cable
- Loop in Loop Out
- 5 Year Product Warranty
- 150 lm/W



General information:

Wattage (W)	60 / 80 / 100
Lumens (lm)	9,000 / 12,000 / 15,000
Efficacy (lm/W)	150
Colour Temperature (K)	3000 / 4000 / 5000
CCT	3CCT
IP Rating	66
IK Rating	8
Class Rating	1
Energy Rating	C
Dimmable	0-10V
L70 Hours	100000
L80 Hours	80000
L90 Hours	50000
Paint Finish (RAL)	9017

Technical information:

Application Location	External
Beam Angle	P55D
Optics	Asymmetric
CRI	70
Input Type	220-240V AC
Driver Type	CC
Operating Temperature From	-40
Operating Temperature To	50
Product Warranty (Years)	5
SDCM	5
Driver Brand	Sosen
Socket	N/A
Frequency (Hz)	50 60
Diffuser Material	Glass
Install Options	BESA/Conduit
Install Type	Flying Lead
Replaceable Driver	Professional
Replaceable LED	Professional
Body Material	Aluminium

Thoresby

Category: Thoresby

Part Number: 421385

Description: Thoresby Floodlight 60W/80W/100W 3CCT IP66 Black
ASY 50x120D P55D



Technical information:

Maintained	Maintained/Non-Maintained
Sensor Technology	Photocell
Sensor Type	On-Off
Standby Power	7.0

